

SPECIFICATIONS

Subject to improvement, modification or change without notice.

LENGTH	Extended.....55" ² Collapsed.....46" ²
WEIGHT	3.1 pounds ²
FREQUENCY	VLF Search.....5.5 kHz Audio Target Response.....495 Hz ³
OPERATING MODES	Search.....VLF Slow Motion Discrimination ³ Pinpoint.....VLF - All Metal No-Motion
SEARCH COIL	Type.....Concentric, Co-Planar Diameter.....8" ⁴ Shielding.....100% E.S.I. ⁵ Interchangeable.....Yes Submersible.....Yes
BATTERIES	9 Volt Transister (Qty. 2) BATTERY LIFE, Carbon Zinc.....20-30 hours ^{2, 6} Alkaline.....40-50 hours ^{2, 6}
WARRANTY	Lifetime Limited Warranty* - *warranty may vary outside of the United States, see your dealer for details Fisher does not warrant suitability to specific use. Fisher shall in no event be liable for any direct or incidental, consequential or indirect damages.

NOTES

1. Subject to improvement or modification without notice
2. Approximate
3. Pulsegate Unipolar Audio Processing. Advanced Fisher circuitry, which allows silent operation below audio threshold tone with no loss in sensitivity.
4. The 1225-X is a motion metal detector. While in search mode, the coil must be moving at least slightly to detect a target.
5. ESI - Electro Static Insulated to reduce certain types of false signals.
6. Use of headphones may increase battery life up to 100%.

ACCESSORIES

STANDARD EQUIPMENT

8" Search Coil
Operating Manual

OPTIONAL EQUIPMENT

Fisher Phones
Stereo Headphones
10.5" Spider Search Coil
5" Search Coil
Hard Carrying Case
Carrying Bag
Coil Covers