

SPECIFICATIONS

Subject to improvement, modification or change without notice.

| | |
|-----------------------------------|---|
| WEIGHT | 3.5 lbs. |
| LENGTH | Extended 52" ¹ Collapsed 42" ² |
| FREQUENCY | VLF-Search 8-2 KHz, Quartz Crystal Controlled Audio Target Response 512 Hz Unipolar ³ |
| SEARCH MODES | Normal Disc VLF-Slow Motion Discrimination ⁴ Iron Disc VLF-Slow Motion Discrimination ⁴ Ground Balanced VLF-Slow Motion All Metal Pinpoint VLF All Metal, No-Motion No Threshold Operation Yes ⁵ |
| OUTPUTS | Low Battery Alert Automatic (LED) Built-in Speaker Yes Stereo Headphone Jack Yes |
| SEARCH COILS | Type Concentric, Co-planar Spider Coil Diameter 8" ⁶ Shielding 100% E.S.I. ⁷ Interchangeable Yes Submersible Yes |
| BATTERIES BATTERY LIFE | (2) 9 Volt Carbon Zinc 15-25 hours ² Alkaline 30-40 hours ² |
| WARRANTY | Lifetime Limited Warranty** **Warranty may vary outside of the U.S. Warranty applies to the Original Purchaser Only. See your dealer for details. |

NOTES

1. Subject to modification without notice.
2. Approximate.
3. PULSEGATE UNIPOLAR AUDIO PROCESSING.
Advanced Fisher circuitry which allows silent operation below the "Audio-Threshold Tone" with no sensitivity loss. (See Note 6 also).
4. The 1270 is a "motion" detector while in the search modes, meaning that the search coil must be moving at least slightly to detect a target.
5. Electro-Static-Insulated to eliminate certain types of false signals.
6. The 1270 can operate silently with no "Threshold Tone" (See Note 3); however, in the "maximum" sensitivity position, a low audible threshold is provided.
7. Fisher does not warrant suitability to specific use. Fisher shall in no event be liable for any direct or, incidental, consequential or indirect damages.

ACCESSORIES

STANDARD EQUIPMENT

8" Search Coil
Operation Manual

OPTIONAL EQUIPMENT -

5" Search Coil
10.5" Search Coil
Coil Covers

Carry Bag
Hard Carrying Case
Fisher Phones
Stereo Phones