FISHER H-SCOPE

SPECIFICATIONS

Subject to improvement, modification or change without notice.

FREQUENCY

1. Multiple-Frequency transmit, Dual Frequency Processing VLF Search [4] ....5 KHz and 15 KHz
2. Target Response:

Iron ID	200 Hz (LO)
Foil	350 Hz (MID LO)
Tabs	450 Hz (MID)
Coin ID	1 KHz (HI)
Auto tone	500 Hz 1 KHz (VCO)
Pinpoint/Depth.	500 Hz 1 Hz (VCO) [5]

LENGTH

Extended..... 51" Collapsed [3]..... 41"

WEIGHT

Complete	3.7 lbs
Control Housing	1.5 lbs
Handle and Coil	2.2 lbs

OPERATING MODES

Target ID VLF Slow Motion [6], silent search discrimination Meter..... Lock on, 7 categories
Auto Tune, VLF -Motion [6], all-metal with threshold tone.

PINPOINT/DEPTH

VLF, all metal, no motion

SEARCH COILS

Type	Concentric, Co-planar Spider Coil
Diameter	8"
Shielding	100% ESI [10]
Interchangeable	Yes
Submersible Coil	Yes

BATTERIES

Drop-in, no wires	Yes
Type	Two, 9-Volt Alkaline [7]
Life	10-20 hours [7]

WARRANTY

Lifetime Limited Warranty* *Warranty may vary outside of the U.S
Warranty applies to the Original Purchaser Only. See your dealer for details.

SPECIAL FEATURES

Manual Ground Adjust	Yes
Manual Threshold Tuning	Auto tune mode only
Wet Sand Operation	Yes [8]
Handle Mount/ Hip Mount	Yes
Audio OutputStereo Jack	Stereo Headphones Optional)
Faint Target Audio Boost	Yes [9]
Speaker	Built in
Tone	4 tones plus bell tone for large shallow targets